

TEMPERATURE RECORDING UNIT

ULT 3..

C ← BUS



APPLICATION

Permits recording four minimum and maximum temperature thresholds for sending alarms to tele-management systems via C-Bus.

FEATURES

- Power supply: 230 V~; Consumption: 2 VA; DIN 53 x 115 modular enclosure; Protection: IP 40.
- Four measurement inputs.
- Adjustable recording interval: 5 ... 240 min.

Code		Description	Suitable sensing elements			Data sheet
			NTC 10 kΩ 0 ... 99 °C	NTC 10 kΩ 0 ... 40 °C	NTC 1 kΩ -40 ... 40 °C	
ULT 328		Temperature recording unit.	2	1	1	T 257
ULT 348		Temperature recording unit.	4	—	—	T 257

ACCESSORIES

Code		Description	Application range	Sensing element	Data sheet
SAA 010		Industrial type temperature detector.	0 ... 99 °C	NTC 10 kΩ	N 115
SAA 001		Industrial type temperature detector.	-40...+40°C	NTC 1 kΩ	N 115
SAE 001		Outside temperature detector.	-40...+40°C	NTC 1 kΩ	N 120
SCH 010		Surface temperature detector.	0 ... 99 °C	NTC 10 kΩ	N 130
SIH 010		Immersion detector with brass pocket.	0 ... 99 °C	NTC 10 kΩ	N 140
SIH 010/Inox		Immersion detector with stain. steel pocket.	0 ... 99 °C	NTC 10 kΩ	N 140
SIH 001		Immersion detector with brass pocket.	-40...+40°C	NTC 1 kΩ	N 140
SIH 001/Inox		Immersion detector with stain. steel pocket.	-40...+40°C	NTC 1 kΩ	N 140
SIR 010		Direct immersion rapid detector.	0 ... 99 °C	NTC 10 kΩ	N 140
SAF 010		Cable-type temperature detector.	0 ... 99 °C	NTC 10 kΩ	N 145
SAF 001		Cable-type temperature detector.	-40...+40°C	NTC 1 kΩ	N 145
STA 010		Temperature detector for air ducts.	0 ... 99 °C	NTC 10 kΩ	N 150
STA 001		Temperature detector for air ducts.	-40...+40°C	NTC 1 kΩ	N 150
SAB 010		Room temperature detector.	0 ... 40 °C	NTC 10 kΩ	N 111
SAB 210		Room temperature detector with key + 1 hour.	0 ... 40 °C	NTC 10 kΩ	N 111
SCB 110		Room temperature detector, with adjuster.	0 ... 40 °C	NTC 10 kΩ	N 111
			-5 ... +5 °C	—	
SCB 210		Room temperature detector with key + 1 hour, with adjuster.	0 ... 40 °C	NTC 10 kΩ	N 111
			-5 ... +5 °C	—	
STT 010		Temperature detector for fan-coil.	0 ... 40 °C	NTC 10 kΩ	N 155
STV 010		Glazed surfaces temperature detector.	0 ... 40 °C	NTC 10 kΩ	N 160