

REVERSIBLE LINEAR ACTUATORS FOR VM2 - VB2 - VVZ - VRS VALVES WITH EMERGENCY CLOSURE


CEQ - CER

APPLICATION

Actuators with linear movement for operating VM2-VB2-VVZ-VRS valves.

FEATURES

- Power supply: 230 - 24 V~; Protection: IP 54.
- 3-wire electric control (Common, Opens, Closes) with emergency closure.
- Max. fluid temperature valve: CEQ = 130 °C; CER = 150 °C.



Code	Power supply V~ (VA)	Emergency shut-off	Speed s / mm	Run max. mm.	Force min. N	Valves (up to DN)				Data sheet
						VVZ	VRS	VM 2	VB 2	
CEQ 078	230 (7)	Down	14	5.5	300	–	–	25	20	M 255
CEQ 074	24 (7)	Down	14	5;5	300	–	–	25	20	M 255
CEQ U078	230 (7)	Up	14	5.5	300	20	40	–	–	M 255
CEQ U074	24 (7)	Up	14	5.5	300	20	40	–	–	M 255
CER 158	230 (7)	Down	15	10	450	–	–	50	50	M 256
CER 154	24 (7)	Down	15	10	450	–	–	50	50	M 256
CER 038	230 (12)	Down	3	10	450	–	–	50	50	M 256
CER 034	24 (12)	Down	3	10	450	–	–	50	50	M 256

ACCESSORIES FOR CLR AND CER

Code	Description
FCR 002	2 limit switches 6 (2) A for CLR and CER.